

STAR SCREEN

METHOR CARRIER



- Different arrangement of the stars offers grain sizes from 0-6 mm up to 0-45 mm
- Screen stars strongly decompose the material and screen even moist, cohesive materials with high throughput and without forming clumps
- Adjustment of incline and rotation speed allows to respond to different material requirements
- Simple reversing allows to release blockages quickly
- Attachment is picked up with the adapter of the Methor and powered by the auxiliary hydraulics
- Integrated support legs allow rapid set down and change to another attachment within minutes without additional equipment
- No support is required in operation, so the machine can be moved during work

STAR SCREEN

DIMENSIONS STAR SCREEN

Length	3520 mm
Width	2170 mm
Height	3000 mm

DISCHARGE HEIGHT

Coarse fraction	2550 mm
Fine fraction	1780 mm

DRIVE STAR SCREEN

Engine type	Hydraulic
-------------	-----------

OTHERS

Weight	1600 kg
--------	---------

INTEGRATED SUPPORT LEGS

METHOR CARRIER WITH STAR SCREEN

Chassis	Tracked chassis
Drive	Diesel hydraulic
Overall weight	16600 kg
Transport width	2520 mm
Transport height	3160 mm
Transport length	11000 mm
Loading height	3150 mm

